



RELIANT™ 600

HEAVY-DUTYLIFT



Designed to meet the special needs of your residents weighing up to 600 lbs., the **Invacare America Reliant™ 600 Heavy-Duty Lift** is secure and sturdy, providing a safe alternative to manual lifting. Both durable and functional, the Reliant 600 Lift is also a reassuring and comfortable resident lift. When answering the needs of every resident is your priority, this is your wisest choice.

Invacare America Reliant™ 600 Lift Features

High lift range allows transfer to high surfaces
Low friction casters significantly improve rollability and contribute to caregiver safety
Designed to meet the needs of the growing bariatric population up to 600 lb.
Manual lowering for instant response to power loss
Unique sling fabric designed to provide the utmost in comfort and strength

Available with power opening base (model # RPL600-2)
Essential device for safe resident handling in hospitals and LTC (long-term care) facilities
Limited warranty includes three years on lift, one year on electric components
Rear locking casters are standard
Manufactured in an ISO13485 facility



RPL600-1: Powered with low base



RPL600-2: Powered with power opening low base



1. **Manual Lowering**

Manual emergency lowering gently and safely lowers the resident in case of total power loss

Essential safety feature

Manual lowering is easy and effortless. Simply insert the end of a ball point pen into the hole marked "emergency" or lift on the accessible ring-pull




2. **Invacare America Reliant™ Digital Scale**

Retrofits on all Reliant 450/600 lifts

Easy to operate, four-button display

Automatic shut-off feature prolongs battery

life Two-year limited warranty



3. **Electronics**

Removable battery box conveniently located on mast features an emergency off button and beeps when battery needs recharged. Requires one 24-volt battery

Quick-release battery eliminates downtime


Anti-entrapment feature stops motion if boom meets resistance while lowering



4. **Charging Station**


Battery can be replaced immediately with second battery in wall-mounted charger

UL listed and CSA certified



1. **Mesh sling model # R140**

2. **Mesh sling with commode opening model # R141**



							
Model #	Height At Sling Hook Up Dimensions	Base Dimensions	Casters	Weight	Weight Capacity	Battery Life Indicator	Emergency Controls
RPL600-1	28"-68" H	4.5"H Clearance 41"W Open 26.5"W Closed 48"L	3.5" Front 5" Rear	112lb.	600lb.	N/A	Stop and Down
RPL600-2	28"-68" H	4.5"H Clearance 41"W Open 26.5"W Closed 48"L	3.5" Front 5" Rear	115lb.	600lb.	N/A	Stop and Down
							
	Battery	Charge Time	Charger Input	Charger Output	Limited Warranty		
RPL600-1	2-24V DC Rechargeable	6 Hours	100-240V AC	29.5DC	3 Years Lift 1 Years Electronics		
RPL600-2	2-24V DC Rechargeable	6 Hours	100-240V AC	29.5DC	3 Years Lift 1 Years Electronics		